OrbitalPRO 4CCT 9W Chrome

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Chrome finish
- Constructed from die cast aluminium alloy & steel
- Fire rated to 30, 60 & 90 minutes
- Tested with insulation cover thickness 270mm
- IP65
- No visible light source
- · Fits into shallow spaces
- Anti-glare indirect light source creating a stylish clean look



SPEC DATA

Product Wattage: 9W Product Lumen: 520 Lumen/W: 58

Kelvin: 2700/3000/4000/6000K

 SDCM:
 6

 CRI:
 80

 Dimmable:
 Yes

 Lifetime (Hours):
 30000

 Beam Angle:
 130°

 Power Factor:
 0.9

Driver Type: Constant Current 200mA


Inrush Current at Start Up: 2.1A
Energy Rating: E
Product Voltage: 220-240V

Product Voltage: 220-24
Hertz: 50/60
Surge Protection (KV): 1.5

Operating Temp.: -20 to 40 Degree

Product Weight (KG): 0.302
Cut-out (mm): Ø97mm
Minimum Cavity Depth (mm): 45mm
Terminal Block: 3 way Quick fit

Class: 2



ACCESSORIES

108097, EM kit standard & self test 2-in-1

