

92542

## Stratus Pro TPA 4000K

### FEATURES

- 5 years (2 years + 3 years) extended warranty
- White paint & opal plastic finish
- Constructed from aluminium alloy & steel & polystyrene
- IP40
- TPA rated
- For use in T-bar ceilings

### SPEC DATA

|                             |                         |
|-----------------------------|-------------------------|
| Product Wattage:            | 40W                     |
| Product Lumen:              | 4000                    |
| Lumen/W:                    | 100                     |
| Kelvin:                     | 4000K                   |
| SDCM:                       | <5                      |
| CRI:                        | >80                     |
| Dimmable:                   | N                       |
| Lifetime (Hours):           | 50000                   |
| Beam Angle:                 | 110°                    |
| Power Factor:               | 0.9                     |
| Driver Type:                | Constant Current 1000mA |
| Inrush Current at Start Up: | ≤ 27A                   |
| Energy Rating:              | E                       |
| Product Voltage:            | 220-240V                |
| Operational Voltage:        | 33-40V DC               |
| Hertz:                      | 50/60                   |
| Surge Protection (KV):      | 1.5                     |
| Operating Temp.:            | -20 to 40 Degree        |
| IK Rating:                  | 03                      |
| Product Weight (KG):        | 1.4                     |
| Class:                      | 3                       |

### ACCESSORIES

- 81007, LED driver constant current dimmable 40W 950mA
- 81744, Stratus suspension kit
- 92823, Stratus surface mount kit
- 91237, Recess clip
- 92544, LED driver constant current 25/30/35/40W selectable
- 108097, EM kit standard & self test 2-in-1
- 108754, Dali driver 700-1050mA selectable

