

CE323

13A Switched Fused Spur Unit with Flex Outlet and Neon

FEATURES

- Our 13A rated fuse spur socket boasts angled in-line terminals with captive screws which provide for quick and easy access and a hassle free installation
- Supplied with fixing screws & white screw covers for sleek appearance
- Flush neon power indicator on faceplate
- Flex outlet with cord grip on the rear
- This has been manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria
- We recommend a minimum mounting box depth of 25mm
- Certified to BS 1363-4

SPECIFICATION DATA

Product Weight:	0.112
Finish:	White
Dimensions:	25.9mm depth x 86mm height x 86mm width
Minimum Mounting Box Depth:	25
Material Construction:	Thermoplastic Urea
IP Rating:	IP20
Switch Type:	Double Pole
Earth Terminals:	2
Socket Type:	-
Terminal Capacity(mm):	6 ² *1/ 4 ² *3/ 2.5 ² *4
Anti Microbial Properties:	Yes
Terminal Arrangement:	Angled-in line
Neon Indicator:	Yes
Warranty:	25 Years
Country of Origin:	China
Standards:	BS 1363-4
EAN:	5017588057420

