CE324 13A Unswitched Fused Spur Unit

FEATURES

• Our 13A rated fuse spur socket boasts angled in-line terminals with captive screws which provide for quick and easy access and a hassle free installation

- Supplied with fixing screws & white screw covers for sleek appearance
- This has been manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria
- We recommend a minimum mounting box depth of 25mm
- Certified to BS 1363-4







SPECIFICATION DATA

| 5 | 0.000 |
|-----------------------------|---|
| Product Weight: | 0.099 |
| Finish: | White |
| Dimensions: | 25.8mm depth x 86mm height x 86mm width |
| Minimum Mounting Box Depth: | 25 |
| Material Construction: | Thermoplastic Urea |
| IP Rating: | IP20 |
| Switch Type: | - |
| Earth Terminals: | 2 |
| Socket Type: | - |
| Terminal Capacity(mm): | 62*1/42*3/2.52*4 |
| Anti Microbial Properties: | Yes |
| Terrminal Arrangement: | - |
| Neon Indicator: | No |
| Warranty: | 25 Years |
| Country of Origin: | China |
| Standards: | BS 1363-4 |
| EAN: | 5017588057086 |

