SE324 13A Unswitched Fused Spur Unit

FEATURES

• Our 13A rated fuse spur socket boasts angled in-line terminals with captive screws which provide for quick and easy access and a hassle free installation

• Supplied with fixing screws & white screw covers for sleek appearance

• This has been manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria

- We recommend a minimum mounting box depth of 25mm
- Certified to BS 1363-4





SPECIFICATION DATA

| Product Weight: | | 0.104 |
|-----------------|---------------------|-----------------------------------|
| Finish: | | White |
| Dimensions | S: | 25.8mm depth x 86mm height x 86mm |
| Minimum N | Nounting Box Depth: | 25 |
| Material Co | instruction: | Thermoplastic Urea |
| IP Rating: | | IP20 |
| Switch Type | e: | - |
| Earth Termi | nals: | 2 |
| Socket Typ | e: | - |
| Terminal Ca | apacity(mm): | 62*1/42*3/2.52*4 |
| Anti Microb | oial Properties: | Yes |
| Terrminal A | rrangement: | Angled-in line |
| Neon Indica | ator: | No |
| Warranty: | | 25 Years |
| Country of | Origin: | China |
| Standards: | | BS 1363-4 |
| EAN: | | 5017588057840 |



width

